

Eastern Wire + Conduit

FIRESTOP Product Specifications

EASTERN'S QUICK ROLL™



May 1, 2004



Applications:

Eastern Quick Roll™ is manufactured for use with EMT conduit and other penetrants. The system is applicable for rated wallboard walls, structural concrete slabs or walls, hollow core concrete slabs, masonry walls, metal deck/concrete composite floors and floor-ceiling assemblies

Product Description:

A unique flexible one piece strip of intumescent material designed to easily fit around new or existing through penetrants in a fire rated assembly. Does not require any special tools, compaction of mineral wool or backer materials.

Eastern Quick Roll™ is one-step system that is a quick, simple and test-proven method of firestopping metallic pipe and other penetrants. The Eastern Quick Roll™ is readily installed in the rough-in stage or as a retrofit; not requiring screws, pull tabs, sealant or compaction of insulation material. The simple installation can be completed by the electrical or data contractor and takes less time than current conventional systems.

No calculation of doses... No guess at compaction!

Common system listings:
Concrete floor: PHV-120-03
Concrete wall: PHV 120-03
Gypsum wall: PV-60-02
Floor-ceiling Assy: PH 60-03

Testing and Approvals:

Eastern Quick Roll™ and is tested to, the rigorous measures of the following organizations:

- ASTM E814
- UL 1479
- ULC CAN4-S115M
- Factory Mutual (FM)

Physicals:

Pre-formed molded intumescent strip

- Flexible PVC based compound
- ½" wide x 3/8" thick x 50' long
- Environmentally stable and resistant to exposure to elevated temperature, humidity and/or immersion in water
- Indefinite shelf life

tyco

*Electrical &
Metal Products*

1-800-483-3473
www.easternwire.com



Eastern Wire + Conduit

FIRESTOP Product Specifications

Rating:

When used as a system, the Eastern Quick Roll™ provides a 1 hour F rating. See UL Directory of products certified for Canada and UL Fire Resistance Directory for further details

Installation Method:

1. Select the proper Eastern Quick Roll™ length from the table provided on package for appropriate conduit size and type.
2. Once the proper length has been determined, cut the Quick roll to length required.
3. Wrap the black intumescent strip around the conduit such that the black intumescent strip will contact the floor, wall or ceiling assembly. Butt seam the ends together and use tape to hold ends together, then tuck the Quick Roll strip into the annular space.

CATALOG NUMBER

DISCRIPTION

QR 50	1/2" X 3/8" X 50'
-------	-------------------

Technical Service:

Eastern Wire + Conduit provide technical support to assist in product selection, proper installation and any other technical questions. System drawings are available for submittal purposes upon request or can be printed from the Technical Page in our website, www.easternwire.com

Local Representative

G T Sales 801-977-9191 fax 801-977-9393

Warranty:

All Royal products are guaranteed for a period of one year from the date of purchase against defects resulting from faulty workmanship or materials. If any such product is found to be defective by reason of faulty workmanship or materials, upon written notice and return of the product, the defective product will be replaced by Royal free of charge, including shipping charges for replacement product. Claims for labor costs and other expenses required to replace such defective product or to repair any damage resulting from the use thereof will not be accepted by Royal. Our liability is limited to the price paid for the defective product. Royal will not be bound by any warranty, other than above set forth, unless such warranty is in writing. This is published in good faith and is believed to be reliable. However, Royal does not represent and/or warrant in any manner the information and suggestions contained on this package. Data presented is the result of laboratory tests.

tyco

Electrical &
Metal Products

1-800-483-3473

www.easternwire.com

