

## Coil/Reel Lengths

Size	Coil	Reel Length
1/2	370	1,200
3/4	250	1,000
	500	
1	250	1,000
	500	5,000
1 1/4	200	1,000
	500	3,200
1 1/2	150	1,000
	350	
2		500
	100	700



## Innerduct Specifications

Size	Part #	Nominal I.D.	Nominal O.D.	Weight (lbs./ft.)	Min. Bend Radius
1/2	PDP0500	0.58	0.83	0.07	2
3/4	PDP0750	0.83	1.04	0.08	2
1	PDP1000	1.05	1.31	0.10	3
1 1/4	PDP1250	1.38	1.65	0.16	3
1 1/2	PDP1500	1.55	1.88	0.20	4
2	PDP2000	2.04	2.35	0.23	4

\* White is also available from stock.

## Fittings



## Reel Dimensions (height x width)

Size	500 Reel	700 Reel	1,000 Reel	1,200 Reel	3,200 Reel	5,000 Reel
1/2	-	-	-	30 x29	-	-
3/4	-	-	30 x29	-	-	-
1	-	-	41 x29	-	-	60 x48
1 1/4	-	-	48 x36	-	60 x48	-
1 1/2	-	-	48 x36	-	-	-
2	48 x32	48 x36	-	-	-	-

## Plenum

Eastern Wire + Conduit's Protect-N-Duct™ Plenum is a UL listed, non-metallic corrugated flexible innerduct for use primarily in plenum applications.

Protect-N-Duct™ Plenum is manufactured from PVDF resin and is listed to UL2024 for plenum optical fiber/communication raceways.

Eastern Wire + Conduit's Protect-N-Duct™ Plenum is listed according to the National Electric Code for Plenum, Riser, and General Purpose optical fiber/telecommunication applications (Article 770 and 800).

All sizes of Eastern's Protect-N-Duct™ Plenum comes complete with a pre-installed 900 pound pull rope. Other specialty tapes are available.

Maximum Flame Propagation 1.50 ft.  
 Peak Optical Smoke Density 0.03  
 Average Smoke Density 0.01  
 Storage -4F to +158F  
 Handling -4F to +104F

# Plenum

1-800-483-3473  
[www.easternwire.com](http://www.easternwire.com)

