

Riser

Reel Dimensions (height x width)

Size	500 Reel	700 Reel	1,000 Reel	1,200 Reel	3,200 Reel	5,000 Reel
1/2	-	-	-	30 x29	-	-
3/4	-	-	30 x29	-	-	-
1	-	-	41 x29	-	-	60 x48
1 1/4	-	-	48 x36	-	60 x48	-
1 1/2	-	-	-	48 x36	-	-
2	48 x32	48 x36	-	-	-	-

Innerduct Specifications

Size	Part #	Nominal I.D.	Nominal O.D.	Weight (lbs./ft.)	Min. Bend Radius
1/2	PDRU0500	0.58	0.84	0.10	5
3/4	PDRU0750	0.83	1.05	0.12	6
1	PDRU1000	1.03	1.32	0.17	6
1 1/4	PDRU1250	1.38	1.66	0.20	7
1 1/2	PDRU1500	1.57	1.90	0.24	8
2	PDRU2000	2.02	2.38	0.26	9

Coil/Reel Lengths

Size	Coil	Reel Length
1/2	370	1,200
3/4	250 500	1,000
1	250 500	1,000 5,000
1 1/4	200 500	1,000 3,200
1 1/2	150 350	1,200
2	100	500 700

Maximum Flame Propagation 6.0 ft.
Storage Temperatures -4F to +158F
Handling Temperatures -4F to +104F

Riser

Eastern Wire + Conduit's Protect-N-Duct™ Riser is a PVC flexible inner duct for use in riser and general-purpose applications. Protect-N-Duct™ Riser is UL listed (UL 2024 standard for riser applications in optical fiber/communication raceways). Protect-N-Duct™ Riser is suitable for use in vertical runs in a shaft or between floors.

Protect-N-Duct™ Riser is listed to the NEC per article 73 and 800 for riser and general-purpose optical fiber/telecommunication applications.

All sizes of Eastern's Protect-N-Duct™ Riser come complete with a pre-installed 900 pound pull rope. Other specialty tapes are available.

Fittings



Eastern stocks a full line of solvent weld and quick snap couplings, terminal adapters and female adapters in sizes 1/2" to 2". (See Page 8)